

## DESCRIPTION

**AURELIA TI** is a range of trunk piston engine oils developed for use in medium speed diesel engines burning residual fuels. **AURELIA TI** combines an exclusive formulation of latest additive technologies, developed by Total research center, and a highly refined base oil to provide an substantial safety margin to cope with the higher stress levels even with the latest and future designs of diesel engines.

## APPLICATIONS

- Highly rated medium speed diesel engines used in marine and stationary power generation applications, burning heavy fuel oil with various qualities and sulphur contents.
- Particularily suitable for low or very low oil consumption engines operating with a poor quality residual fuel.
- Bearings and stern-tubes.
- Reduction gear lubrication.

## PROPERTIES

- API service : exceeds CF specification
- Ensures outstanding cleanliness of the hot and cold parts of the engine, due to improved detergency and dispersancy capabilities.
- Reduced build-up heavy deposits in the engine leading to a reduction in maintenance costs.
- Excellent resistance to the negative effects of contamination with residual fuel.
- Excellent thermal resistance and high temperature oxidation resistance.
- Excellent control of viscosity increase leading to reduced top-ups.
- Very good water resistance and an outstanding demulsibility capacity leading to maintain the engine performance and to remove the water rapidly after a water ingress.
- Very good wear protection and very good oil film strength at extreme pressures.

## APPROVALS

The **AURELIA TI** range hold approvals from all major medium speed engine manufacturers such as WÄRTSILÄ, MAN diesel, Caterpillar MaK, Yanmar, Daihatsu, HiMSEN, Rolls Royce...

## CHARACTERISTICS

CHARACTERISTICS	METHODS	UNITS	AURELIA TI	
			3040	4040
S.A.E. Grade			30	40
Density at 15 °C	ISO 3675	kg/m <sup>3</sup>	910	910
Kinematic viscosity at 40 °C	ISO 3104	mm <sup>2</sup> /s	112	140
Kinematic viscosity at 100 °C	ISO 3104	mm <sup>2</sup> /s	12	14
Flash Point (COC) ASTM D 92	ASTM D 92	°C	>or= 230	>or= 230
Pour Point	ISO 3016	°C	- 9	- 9
BN (ex TBN) ASTM D 2896	ASTM D 2896	mgKOH/g	40	40

Characteristics of this chart are indicative typical values

## *HANDLING, HEALTH AND SAFETY*

Lubricants consisting of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available on [www. quickfds.com](http://www.quickfds.com) or [www.lubmarine.com](http://www.lubmarine.com).

The values shown above are typical values at the date of publication. TOTAL Lubmarine reserves the right to change these typical values without prior notice.



TOTAL LUBRIFIANTS  
562 avenue du Parc de l'Île – 92029 Nanterre Cedex  
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92  
[www.lubmarine.com](http://www.lubmarine.com) - [rm.tma-diagomarplus@total.com](mailto:rm.tma-diagomarplus@total.com)

LUBMARINE 302/5 GB – 1006