

DISOLA M3015 – M4015 – M5015 *Lubmarine*

DESCRIPTION

Marine oils especially designed for the lubrication of the high and medium speed Diesel engines.

APPLICATIONS

- Turbocharged and naturally aspirated main and auxiliary engines of all types and all ratings, running on Gas Oil or Marine Diesel Oil (ISO 8217 DMX and DMA).
- **DISOLA M 5015** can be used for the running-in of slow speed 2-stroke crosshead engines.
- Bearings and stern-tubes.
- Reduction gear lubricating.

PROPERTIES

- API service: CF.
- Good thermal stability.
- Good detergent properties at high temperatures.
- Good dispersing properties at low temperatures.
- Good wear protection.
- Good oil film strength at extreme pressures.
- Excellent water resistance.
- Excellent capacity for centrifuging and for separating out water and insolubles.
- Excellent filtration capacity.
- Very good acidic neutralisation capability

APPROVALS

DISOLA M 4015 meets the French Navy specification STM 7251A level NATO O 278.

Lubricants in the **DISOLA M** range satisfy the requirements and recommendations of the major engine manufacturers. They have proved their worth in thousands of engines of many different types, operating in all conditions.

CHARACTERISTICS

CHARACTERISTICS	METHODS	UNITS	DISOLA M		
			3015	4015	5015
S.A.E. Grade			30	40	50
Density at 15 °C	ISO 3675	kg/m ³	900	900	900
Kinematic viscosity at 40 °C	ISO 3104	mm ² /s	110	145	230
Kinematic viscosity at 100 °C	ISO 3104	mm ² /s	12	14.2	19.7
Flash Point (COC)	ASTM D 92	°C	> 220	> 230	> 240
Pour Point	ISO 3016	°C	- 9	- 9	- 9
BN	ASTM D 2896	mgKOH/g	14	14	14

Characteristics of this chart are indicative typical values

HANDLING, HEALTH AND SAFETY

Lubricants consisting of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available on [www. quickfds.com](http://www.quickfds.com) or www.lubmarine.com.

The values shown above are typical values at the date of publication. TOTAL Lubmarine reserves the right to change these typical values without prior notice.



TOTAL LUBRIFIANTS
562 avenue du Parc de l'Île – 92029 Nanterre Cedex
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92
www.lubmarine.com - rm.tma-diagomarplus@total.com

LUBMARINE 24/4GB - 1006