

DESCRIPTION

Extreme pressure lithium/calcium grease with molybdenum disulfide.

APPLICATIONS

- General machinery lubrication.
- Bearings subject to heavy and shock loading.
- Slow oscillating bearings under extreme pressure.
- All plain sleeve, and guide bearings.
- Journal bearings of the bush type.
- Operating temperature range within minus 25°C to 130°C.
- **MULTIS MS2** is recommended for long intervals greasing without any change of its properties or characteristics.

PROPERTIES

- Very high load carrying capacity and anti-wear properties.
- Assure a low coefficient of friction.
- Good water resistance.
- Very high resistance to oxidation.
- Excellent protection against rust and corrosion.
- Further to ISO 6743-9 specification, **MULTIS MS 2** meets L-XBCEB2 classification.
- Further to DIN 51502 specification, **MULTIS MS 2** meets MPF2K-25 classification.

CHARACTERISTICS

CHARACTERISTICS	METHODS	UNITS	MULTIS MS2
N.L.G.I. Grade	ASTM D 217/DIN 51 818	-	2
Colour	Visual	-	Grey
Texture	Visual	-	Smooth
Thickener		-	Lithium/calcium
Worked Penetration 25 °C	ASTM D 217/DIN51 818	0.1 mm	265/295
Dropping Point	IP 396/DIN ISO 2176	°C	> 185

Characteristics of this chart are indicative typical values

HANDLING, HEALTH AND SAFETY

MULTIS MS2 grease contains high refined mineral based products with additives.

In normal conditions of use, this grease presents no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available on [www. quickfds.com](http://www.quickfds.com) or www.lubmarine.com.

The values shown above are typical values at the date of publication. TOTAL Lubmarine reserves the right to change these typical values without prior notice.



TOTAL LUBRIFIANTS
562 avenue du Parc de l'Île – 92029 Nanterre Cedex
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92
www.lubmarine.com - rm.tma-diagomarplus@total.com

LUBMARINE 85/2GB - 1006