

DESCRIPTION

Very viscous inhibited paraffinic mineral oil.

APPLICATIONS

- Steam cylinder lubricating oil.
- Bearings.
- Reduction gears.

PROPERTIES

- Good anti-rust properties.
- Good anti-corrosion properties.
- High thermal stability.

CHARACTERISTICS

CHARACTERISTICS	METHODS	UNITS	CIRKAN RO 460
Density at 15 °C	ISO 3675	kg/m ³	900
Kinematic viscosity at 40 °C	ISO 3104	mm ² /s	429.5
Kinematic viscosity at 100 °C	ISO 3104	mm ² /s	29.93
Flash Point (COC)	ASTM D 92	°C	312
Pour Point	ISO 3016	°C	- 15

Characteristics of this chart are indicative typical values

HANDLING, HEALTH AND SAFETY

Lubricants consisting of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available on [www. quickfds.com](http://www.quickfds.com) or www.lubmarine.com.

The values shown above are typical values at the date of publication. TOTAL Lubmarine reserves the right to change these typical values without prior notice.



TOTAL LUBRIFIANTS
562 avenue du Parc de l'Île – 92029 Nanterre Cedex
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92
www.lubmarine.com - rm.tma-diagomarplus@total.com

LUBMARINE 93/2GB - 1006