

PRESLIA 68 **Product name:** Page: 1/6

SDS n°:31453-33 Version:4.02 Version of :2009-12-07

This sheet supersedes the one dated :2008-11-09

PRODUCT LABELS

LABELLING (standard or EU): Not concerned

R-phrases: None S-phrases: None

TRANSPORT LABELLING: Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product: PRESLIA 68

Code No.: 694

Product application: Turbine oil

TOTAL LUBRIFIANTS Supplier:

562, Avenue du Parc de l'Ile 92029 Nanterre Cedex - France Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

rm.msds-lubs@total.com

See local details at end of sheet:

2. HAZARDS IDENTIFICATION

The product is not classified as dangerous in accordance with directive 1999/45/EC.

Health effects: This product does not present a danger of intoxication.

Environmental impact: Do not discharge this product into the environment.

Physico-chemical hazards: No specific risk of fire or explosion under normal conditions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature: Petroleum-derived severely refined mineral-base product

in which the polycyclic aromatic hydrocarbons (PCA or PAH) content, measured by IP

346, is less than 3%

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
1,2,4-trimethylbenzene	202-436-9	95-63-6	<0,1 %	Xn ,N	R-10, 20, 36/37/38, 51/53

See section 16 for explanations of R-phrases:

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of

Transport the person into fresh air, keep warm and allow to rest.



Product name: PRESLIA 68 Page: 2/6

SDS n° :31453-33 Version :4.02 Version of :2009-12-07

This sheet supersedes the one dated :2008-11-09

Ingestion: Possible risk of vomiting and diarrhoea.

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.

Give nothing to drink

Skin contact: Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and water.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.

Aspiration: If the product is believed to have entered the lungs (in case of vomiting, for example),

take the person to hospital for immediate care.

5. FIRE FIGHTING MEASURES

Flash point: See heading 9

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

- not recommended:

Do not use water jets (stick jets) for extinguishing fire, as this may help the spread of

flames.

Specific hazards: Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled.

Vapours can build explosive mixtures with air.

Vapours are heavier than air and may spread on the ground to sources of ignition.

Protective measures for firefighters: Insulated breathing apparatus must be worn in confined premises with heavy

concentrations of fumes and gases.

Other: All combustion residues and contaminated water from fire-fighting should be disposed of

according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

Personal protection: Ensure good ventilation.

Remove sources of ignition. Do not smoke.

After spillage / leakage : - On land

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil.

Recover with mechanical means such as pumps and skimmers.

- On water:

Floating absorbant material, then mechanical recovery.

If the product is spilt into rivers or sewers, notify the authorities of the possible presence

of surface effluent.

Spill cleanup methods : - Recovery:

Contain and collect the spilled product. Use sand on the surfaces concerned if necessary. Contain and collect the spilled product with sand or any other inert absorbent material. In the event of a major spill, inform the relevant authorities if the situation cannot be brought under control rapidly and efficiently.

- Elimination:

Dispose of waste in compliance with regulations.

Avoid discharge of the material in a stream or a sewer or cause ground contamination.



Product name: PRESLIA 68 Page: 3/6

SDS n° :31453-33 Version :4.02 Version of :2009-12-07

This sheet supersedes the one dated :2008-11-09

7. HANDLING AND STORAGE

HANDLING:

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure risk, notably to products

in use or to wastes.

Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to remove

spills which become soaked with product.

Avoid accumulation of these: they are to be disposed off safely after use.

Precautions: Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes

onto hot machine parts and electrical contacts (on joint failure, for example).

STORAGE:

Technical measures: Make the necessary arrangements to prevent water and soil pollution.

Storage precautions : - Suitable:

Store at ambient temperature, protected against contact with water and moisture, and

away from any source of ignition. Keep containers closed when not in use - To be avoided:

Do not store exposed to the elements.

Incompatible products: Dangerous reaction with strong oxidizing agents.

Packaging materials: - Recommended:

Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures: Use the product in a properly ventilated atmosphere.

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not

suffocating and/or wear recommended equipment.

Composant	N°. CAS	Référence	VME 8 h	VLE 15 mn	Date
1,2,4-trimethylbenzene	95-63-6	VLEP France	100 (20) mg/m3 (ppm)	250 (50) mg/m3 (ppm)	

Hand protection : Impermeable hydrocarbon-proof gloves.

recommended material: nitrile, neoprene.

The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to

be found out from the manufacturer of the protective gloves themselves.

The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing

suitable gloves, it is recommended that the user tests the gloves.

Eye protection: Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection:

As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when

handling drums).

Don't wear rings, watches or anything similar which can retain the product and may give

rise to skin conditions.



PRESLIA 68 **Product name:** Page: 4/6

SDS n°:31453-33 Version:4.02 Version of :2009-12-07

This sheet supersedes the one dated :2008-11-09

Hygienic work practices: Avoid prolonged and repeated contact with the skin, especially with used or waste

Immediately remove all soiled or stained clothing.

If the product comes into contact with the skin, wash the affected area immediately and

copiously with soap and water.

Do not use abrasives, solvents or fuels.

Do not dry hands with rags that have been contaminated with product.

Do not put product contaminated rags into workwear pockets.

Do not eat, drink or smoke whilst handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid.

Colour: Yellow to amber.

Odour: Characteristic for oil.

Density/specific gravity: 887 Kg/m3

Temperature (°C) 15

Flash point: > 220 °C OC (Open cup).

Température d'auto-inflammation : > 250 °C (ASTM E 659-78)

Partition coefficient (log Pow): Log Pow > 6

Temperature (°C) (20°C)

Viscosity: 68 mm2/s

Temperature (°C) 40

10. STABILITY AND REACTIVITY

Stability: The product is stable at normal storage, handling and use temperatures.

Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static electricity

Materials to avoid: Avoid contact with strong oxidizers

Hazardous decomp. products: Incomplete combustion and thermolysis produces potentially toxic gases such as carbon

monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect:

Inhalation, comments: - Inhalation :

Not classified according to the criteria of classification in force.

Inhalation of high concentrations of vapour or aerosols may cause irritation of the upper

respiratory tract.

Skin contact, comments: - Contact with skin:

Not classified according to the criteria of classification in force.

Ingestion, comments: Swallowing the product can cause serious gastric lesions.

In case of ingestion of small quantities, no important effect observed. in case of ingestion

of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

Skin contact: Characteristic skin affections (oil blisters) may develop following prolonged and repeated

exposure through contact with stained clothing



Product name: PRESLIA 68 Page: 5/6

SDS n° :31453-33 Version :4.02 Version of :2009-12-07

This sheet supersedes the one dated :2008-11-09

Sensitization: To our knowledge, the product does not cause aggravated sensitivity.

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity: Experimental data on the finished product are not available.

It is considered to present a little danger for aquatic life.

no information available for used product

Mobility: - Air:

there is a slow loss by evaporation.

- Soil:

Given its physical and chemical characteristics, the product generally shows little

mobility in the ground.

- Water:

The product is insoluble; it spreads on the surface of the water

Persistence and degradability: No experimental information about the finished product.

However the "mineral oil" fraction of the new product is intrinsically biodegradable.

Some components of the product may not be biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in a safe manner, in accordance with local regulations.

If need be, collection by an authorised waste contractor and regeneration or incineration

at an approved installation.

Waste class: 13 02 05

The waste classification is dependant on the composition of the product at the time of

disposal.

The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the

waste classification should be in arrangement with the authorised waste disposal

company.

Disposal of contaminated packaging: Proceed in compliance with the prevailing regulations.

14. TRANSPORT INFORMATION

Not concerned by transport regulations RID/ADR, ADNR, IATA, IMDG.

Road (ADR) / Rail (RID):

Class: Not restricted for transport.

Transport by barge (ADNR):

Marine (IMO-IMDG):

Air (ICAO/IATA):

15. REGULATORY INFORMATION

Not applicable

Risk phrases : None
Safety phrases : None

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

Social Security code: - Art. L 461-6, Art. D.461-1, annexe A, n° 601

Table of occupational illnesses and diseases No. 36



Product name: PRESLIA 68 Page: 6/6

SDS n° :31453-33 Version :4.02 Version of :2009-12-07

This sheet supersedes the one dated :2008-11-09

Labor code : - Art. R.4624-19 à R.4624-20, arrêté du 11.07.77(surveillance médicale renforcée).

16. OTHER INFORMATION

For France, in case of poisoning call the Antipoison Centre (if possible in your area) and/or the SAMU (15), see ORFILA number below - Tel: Angers 02.41.48.21.21 - Bordeaux 05.56.96.40.80 - Lille 03.20.44.44.44 - Lyon 04.72.11.69.11 - Marseille 04.91.75.25.25 - Nancy 03.83.32.36.36 - Paris 01.40.05.48.48 - Rennes 02.99.59.22.22 - Strasbourg 03.88.37.37.37 - Toulouse 05.61.77.74.47 This safety data sheet complies with article 31 of the REACH directive 1907/2006/EC

Explanations of R-phrases in section 2: R-10 Flammable.

R-20 Harmful by inhalation.

R-36/37/38 Irritating to eyes, respiratory system and skin.

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Revision date: 2009-12-07 Supersedes the data sheet of: 2008-11-09

* Information revised since the previous version of the SDS:

SDS No.: 05b-0j2yujf-02

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.