

Safety Data Sheet			
Product name :	PRESLIA 100	Page : 1/e	
SDS n° :31452-33	Version :5.01	Version of : 2008-11-09 This sheet supersedes the one dated : 2003-10-29	
PRODUCT LABELS			
LABELLING (standard or EU):	Not concerned		
R-phrases :	None		
S-phrases :	None		
TRANSPORT LABELLING:	Not applicable.		
1. IDENTIFICATION OF THE SU	BSTANCE/PREPARATION AND OF 7	THE COMPANY UNDERTAKING	
Name of the product :	PRESLIA 100		
Code No. :	691		
Product application :	Turbine oil		
Supplier :	TOTAL LUBRIFIANTS 562 avenue du Parc de l'Ile 92029 Nanterre CEDEX Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71 E-mail : rm.msds-lubs@total.com		
See local details at end of sheet :			
2. HAZARDS IDENTIFICATION			
Health effects :	This product does not present a dat	nger of intoxication.	
Environmental impact :	Do not discharge this product into	the environment.	
	No specific risk of fire or explosion		

### PREPARATION

Chemical nature :

Petroleum-derived severely refined mineral-base product in which the polycyclic aromatic hydrocarbons (PCA or PAH) content, measured by IP 346, is less than 3%

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Alkyl phenol			<0,2 %	Xi ,N	R-38, 51/53
Di-t-butyl-p-cresol	204-881-4	128-37-0	<0,2 %	Xi ,N	R-38, 51/53

See section 16 for explanations of R-phrases :

### 4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation :

Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the throat.

Transport the person into fresh air, keep warm and allow to rest.



# Safety Data Sheet

Product name :	PRESLIA 100	Page : 2/6	
SDS n° :31452-33	Version :5.01	Version of : 2008-11-09 This sheet supersedes the one dated : 2003-10-29	
Ingestion :	Possible risk of vomiting and diarr Do not induce vomiting to avoid th Give nothing to drink	hoea. e risk of aspiration into the respiratory tract.	
Skin contact :	Immediately remove all soiled or stained clothing. Wash the affected area immediately and repeatedly with soap and water.		
Eye contact :	Keep eyes open and rinse immedia	Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.	
Aspiration :	If the product is believed to have entered the lungs (in case of vomiting, for example), take the person to hospital for immediate care.		
5. FIRE FIGHTING MEASURES			
Flash point: See heading 9			
Extinguishing media :	<ul> <li>suitable:</li> <li>Foam, carbon dioxide (CO2), powered of the commended:</li> <li>Do not use water jets (stick jets) for flames.</li> </ul>	ler. r extinguishing fire, as this may help the spread of	
Specific hazards :	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled. Vapours can build explosive mixtures with air. Vapours are heavier than air and may spread on the ground to sources of ignition.		
Protective measures for firefighters :	Insulated breathing apparatus must be worn in confined premises with heavy concentrations of fumes and gases.		
Other :	All combustion residues and contaminated water from fire-fighting should be disposed of according to local regulations.		
6. ACCIDENTAL RELEASE MEASU	RES		
See sections 8 and 13.			
Personal protection :	Ensure good ventilation. Remove sources of ignition. Do no	t smoke.	

After spillage / leakage :

Spill cleanup methods :

- Recovery:

- On land:

- On water:

of surface effluent.

Contain and collect the spilled product. Use sand on the surfaces concerned if necessary. Contain and collect the spilled product with sand or any other inert absorbent material. In the event of a major spill, inform the relevant authorities if the situation cannot be brought under control rapidly and efficiently. - Elimination: Dispose of waste in compliance with regulations.

If the product is spilt into rivers or sewers, notify the authorities of the possible presence

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil.

Recover with mechanical means such as pumps and skimmers.

Floating absorbant material, then mechanical recovery.

Avoid discharge of the material in a stream or a sewer or cause ground contamination.



	Safety Data Shee	t
Product name :	PRESLIA 100	Page : 3/6
SDS n° :31452-33	Version :5.01	Version of : 2008-11-09 This sheet supersedes the one dated : 2003-10-29
7. HANDLING AND STORAGE		
HANDLING :		
Prevention of user exposure :	Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk. Make all the necessary arrangements in order to reduce exposure risk, notably to products in use or to wastes. Keep away from combustible substances; keep away from food and beverages.	
Prevention of fire and explosion :	Empty containers may contain flammable or explosive vapours. There is a fire hazard associated with rags, paper or any other material used to remove spills which become soaked with product. Avoid accumulation of these: they are to be disposed off safely after use.	
Precautions :	Avoid static electricity build up with connection to earth. Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example).	
STORAGE :		
Technical measures :	Make the necessary arrangements to prevent water and soil pollution.	
Storage precautions :	<ul> <li>Suitable:</li> <li>Store at ambient temperature, protected against contact with water and moisture, and away from any source of ignition.</li> <li>Keep containers closed when not in use</li> <li>To be avoided:</li> <li>Do not store exposed to the elements.</li> </ul>	
Incompatible products :	Dangerous reaction with strong oxidizing agents.	
Packaging materials :	- Recommended: Use only hydrocarbon-resistant containers, joints, pipes, etc. Keep in original container if possible.	

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures :	Use the product in a properly ventilated atmosphere. When working on enclosed place (tanks, reservoirs), make sure that atmosphere is not suffocating and/or wear recommended equipment.
Hand protection :	Impermeable hydrocarbon-proof gloves. recommended material: nitrile , neoprene. The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves themselves. The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing suitable gloves, it is recommended that the user tests the gloves.
Eye protection :	Goggles, in case of risk of splashing.
Skin and body (other than the hands) protection	n : As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when
	handling drums).

Don't wear rings, watches or anything similar which can retain the product and may give rise to skin conditions.



# **Safety Data Sheet**

Product name :	PRESLIA 100	Page : 4/6	
SDS n° :31452-33	Version :5.01	Version of : 2008-11-09 This sheet supersedes the one dated : 2003-10-29	
Hygienic work practices :	Avoid prolonged and repeated contact with the skin, especially with used or waste product Immediately remove all soiled or stained clothing. If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. Do not eat, drink or smoke whilst handling the product.		
9. PHYSICAL AND CHEMICAL PR	OPERTIES		
Appearance :	Liquid.		
Colour :	Yellow to amber.		
Odour :	Characteristic for oil.		
Density/specific gravity :	887 Kg/m3 Temperature (°C) 15		
Flash point :	> 220 °C OC (Open cup).		
Température d'auto-inflammation :	> 250 °C (ASTM E 659)		
Partition coefficient (log Pow) :	Log Pow > 6 Temperature (°C) (20°C)		
Viscosity :	100 mm2/s Temperature (°C) 40		
10. STABILITY AND REACTIVITY			
Stability :	The product is stable at normal stora	age, handling and use temperatures.	
Conditions to avoid :	Heat (temperatures above flach point) sparks ignition points flames static electricity		

Conditions to avoid :Heat (temperatures above flash point), sparks, ignition points, flames, static electricityMaterials to avoid :Avoid contact with strong oxidizersHazardous decomp. products :Incomplete combustion and thermolysis produces potentially toxic gases such as carbon<br/>monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect :	
Inhalation, comments:	<ul> <li>Inhalation : Not classified according to the criteria of classification in force.</li> <li>Inhalation of high concentrations of vapour or aerosols may cause irritation of the upper respiratory tract.</li> </ul>
Skin contact, comments:	- Contact with skin : Not classified according to the criteria of classification in force.
Ingestion, comments:	Swallowing the product can cause serious gastric lesions. In case of ingestion of small quantities, no important effect observed. in case of ingestion of larger amounts: abdominal pain, diarrhea,
CHRONIC TOXICITY OR LONG-TERM T	OXICITY :

 Skin contact :
 Characteristic skin affections (oil blisters) may develop following prolonged and repeated exposure through contact with stained clothing



Product name :	PRESLIA 100	Page : 5/
SDS n° :31452-33	Version :5.01	Version of : 2008-11-0 This sheet supersedes the one dated : 2003-10-2
Sensitization :	To our knowledge, the product do	bes not cause aggravated sensitivity.
12. ECOLOGICAL INFORMATION		
Comments about ecotoxicity :	Experimental data on the finished product are not available. It is considered to present a little danger for aquatic life. no information available for used product	
Mobility :	<ul> <li>Air:</li> <li>there is a slow loss by evaporation.</li> <li>Soil:</li> <li>Given its physical and chemical characteristics, the product generally shows little mobility in the ground.</li> <li>Water:</li> <li>The product is insoluble; it spreads on the surface of the water</li> </ul>	
Persistence and degradability :	No experimental information about the finished product. However the "mineral oil" fraction of the new product is intrinsically biodegradable. Some components of the product may not be biodegradable.	
13. DISPOSAL CONSIDERATIONS		
Waste disposal :	Dispose of in a safe manner, in accordance with local regulations. If need be, collection by an authorised waste contractor and regeneration or incineration at an approved installation.	
Waste class :	The waste classification is dependent on the composition of the product at the time of disposal. The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the authorised waste disposal company.	
	Proceed in compliance with the prevailing regulations.	

Road (ADR) / Rail (RID) :

Class :

Not restricted for transport.

Transport by barge (ADNR) :

Marine (IMO-IMDG) :

Air (ICAO/IATA) :

## **15. REGULATORY INFORMATION**

Not applicable Risk phrases : Safety phrases :

None None



#### PRESLIA 100 **Product name :** Page : 6/6 SDS n° :31452-33 Version :5.01 Version of : 2008-11-09 This sheet supersedes the one dated : 2003-10-29 EU directives : Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC). This product fulfills the requirements of the European directives : 76/769/EEC 2000/53/EC 2002/95/EC 2002/96/EC 2003/11/EC Social Security code : - Art. L 461-6, Art. D.461-1, annexe A, n° 601 Table of occupational illnesses and diseases No. 36 Labor code : - Art. R 241-50, decree of 07.11.1977 (special medical surveillance). **16. OTHER INFORMATION** Explanations of R-phrases in section 2 : R-38 Irritating to skin. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Revision date: 2008-11-09 2003-10-29 Supersedes the data sheet of: \* Information revised since the previous version of the SDS : SDS No. : 05c-0j2yujf-03

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

# **Safety Data Sheet**